Australian Standard™

Hydraulic shoring and trench lining equipment



This Australian Standard was prepared by Committee ME-082, Shoring and Trench Lining. It was approved on behalf of the Council of Standards Australia on 22 June 2004. This Standard was published on 2 June 2005.

The following are represented on Committee ME-082:

Australian Industry Group Civil Contractors Federation Construction, Forestry, Mining and Energy Union Institution of Engineers Australia Master Plumbers and Mechanical Services Association of Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards $^{\text{\tiny TM}}$ and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to the Chief Executive, Standards Australia, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

Hydraulic shoring and trench lining equipment

First published as AS 5047-2005.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia, GPO Box 5420, Sydney, NSW 2001, Australia ISBN 0 7337 6750 8 $\,$

AS 5047—2005

PREFACE

This Standard was prepared by the Standards Australia Committee ME-082, Shoring and Trench Lining.

The objective of this Standard is to provide a specification for hydraulic shoring and trench lining equipment that achieves an acceptable level of safety, for reference by manufacturers, suppliers, users and regulators.

Statements expressed in mandatory terms in notes to tables are deemed to be requirements of this Standard.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

		Page
FOREW	ORD	5
SECTIO	ON 1 SCOPE AND GENERAL	
1.1	SCOPE	6
1.2	NEW DESIGNS, INNOVATIONS AND DESIGN METHODS	
1.3	NORMATIVE REFERENCES	
1.4	TERMS AND DEFINITIONS	
1.5	SYMBOLS	
1.6	DESIGNATION	
1.7	DECLARATION OF CONFORMITY	
1.8	MARKING	
SECTIO	ON 2 MATERIALS	
2.1	GENERAL	30
2.2	FASTENERS	30
2.3	MINIMUM ELONGATION	
2.4	SPECIAL REQUIREMENTS FOR HYDRAULIC RAMS	30
2.5	FLEXIBLE HYDRAULIC HOSES	
SECTIO	N 3 STRUCTURAL COMPONENTS	
3.1	GENERAL	32
3.2	DESIGN PARAMETERS	32
3.3	PARTIAL SAFETY FACTORS	33
3.4	CONFIGURATION OF LOAD	33
3.5	MINIMUM VALUE OF CHARACTERISTIC RESISTANCES	37
3.6	DEFLECTION	37
3.7	HANDLING AND RESTRAINING POINTS (see Figure 13)	37
3.8	WALER OR SOLDIER RAIL TO STRUT CONNECTION	38
3.9	WALER OR SOLDIER STRUTS	38
3.10	RESTRAINING CHAIN	39
3.11	HYDRAULIC BRACING FRAME LEG AND HYDRAULIC RAM LEG	40
3.12	WALER RAIL	40
3.13	SOLDIER RAIL	40
SECTIO	ON 4 HYDRAULIC COMPONENTS	
4.1	GENERAL	41
4.2	HYDRAULIC RAMS	
4.3	MANUFACTURING TOLERANCES FOR RAMS	
4.4	MOUNTING FASTENERS OR PINS	
4.5	BUCKLING RESISTANCE OF PISTON ROD	
4.6	HYDRAULIC SHORING FLUID	
4.7	RAM ACCEPTANCE TEST (PRE-DELIVERY TESTING)	
4.8	VALVES AND HYDRAULIC FITTINGS	
4.9	HYDRAULIC PUMP	
SECTIO	N 5 INSTRUCTION MANUAL	
5.1	GENERAL	
5.2	SPECIFICATION OF A PUMP AND RESERVOIR	
5 3	DATA	46

		Page
5.4	SPECIFICATIONS FOR ANCILLARY ITEMS	
5.5	INFORMATION ABOUT USE	
5.6	MAINTENANCE	
5.7	RAM SPECIFICATION	47
5.8	ENVIRONMENTAL, HEALTH, SAFETY AND POTENTIAL HAZARD	
	CONSIDERATIONS	51
	ON 6 ASSESSMENT BY CALCULATION OR TEST	
6.1	GENERAL	
6.2	CHOICE OF TESTING OR CALCULATION	
6.3	ASSESSMENT BY CALCULATION	
6.4	ASSESSMENT BY TESTING	53
6.5	EVALUATION OF LOAD-BEARING CAPACITY AND STIFFNESS	
	FROM TESTING METALLIC ASSEMBLIES AND COMPONENTS	56
4 DDEN	TELODO	
APPEN		
A	PARTIAL SAFETY FACTORS	66
В	RELATING CHARACTERISTICS RESISTANCES TO PERMISSIBLE	
	WORKING RESISTANCES GIVING VALUES FOR USE	
	IN CALCULATIONS	
C	EXAMPLES OF LOAD CURVES	
D	HYDRAULIC RAM ACCEPTANCE TEST	
E	DESIGNATION CHECK LIST	
F	DOCUMENTATION OF TEST RESULTS	80
G	EXAMPLE FOR THE DETERMINATION OF AN APPROXIMATION	
	FUNCTION, OF THE QUOTIENT (q_e) FOR THE DISSIPATION	
	OF ENERGY AND OF THE PARTIAL SAFETY FACT (γ_{R2})	82
Н	EXAMPLE FOR THE STATISTICAL EVALUATION OF TEST RESULTS	
	AND THE DETERMINATION OF THE NOMINAL CHARACTERISTIC	
	VALUE OF THE RESISTANCE	
I	EXAMPLE FOR THE EVALUATION OF STIFFNESS	88

5 AS 5047—2005

FOREWORD

Hydraulically operated shoring systems comprise prefabricated equipment to provide primary support to the side of excavations. This Standard covers three types of equipment whose resistance and adjustment is hydraulic or by a combination of hydraulic and mechanical means, as follows:

- (a) Hydraulic bracing frames.
- (b) Hydraulic waler frames.
- (c) Hydraulic soldier sets.

A variety of components when assembled form a full system. The prefabricated components are used to make assemblies of different dimensions and structural capacities.

Hydraulically operated shoring equipment has a limitation in use in that it is dependent on a competent person relating soil conditions to the use of the equipment.

This Standard gives specific requirements on the main characteristics of hydraulically operated pumps, hoses and associated equipment, but does not provide requirements for their specification or assessment.

Hydraulically operated shoring equipment is frequently used in conjunction with supplementary equipment, e.g., sheet piling, trench sheeting, knee braces and intermediate bracing struts. Such supplementary equipment is not covered in the Scope of this Standard.

The characteristic resistance values specified in this Standard form a reference level.

Appendix A gives information about the values of partial safety factors for materials (γ_M) and partial safety factor for actions (γ_F). Appendix B gives information on the application of characteristic resistance values to a safe working value.

Hydraulic bracing frames have a restriction limiting the length of a single leg to 20 m. Longer lengths of hydraulic frame legs are possible, but these may require an engineering design input that is not covered in this Australian Standard.

Statements expressed in mandatory terms in notes to Tables and Figures are deemed to be requirements of this Standard.

STANDARDS AUSTRALIA

Australian Standard Hydraulic shoring and trench lining equipment

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies constructional and structural requirements for hydraulically operated shoring systems made from steel and aluminium for groundwork support. It also specifies methods of calculation and test to assess compliance with this Standard. It specifies minimum characteristic resistance for equipment and is limited to assemblies with components having hydraulic rams (see Note 1).

Materials other than steel and aluminium are not precluded; however, this Standard does not specify methods of assessment for equipment made of these materials.

This Standard also provides information on some of the main characteristics of hydraulically operated pumps, hoses and associated equipment, but does not cover assessment of these items.

NOTES:

- 1 Assemblies without hydraulic rams may be designed in accordance with AS 4100.
- 2 Information on the values of partial safety factors is given in Appendix A.
- 3 Information on the application of characteristic resistance values is given in Appendix B.

1.2 NEW DESIGNS, INNOVATIONS AND DESIGN METHODS

This Standard does not preclude the use of materials, designs, methods of assembly, procedures and the like which do not comply with a specific requirement of this Standard, or are not mentioned in it, but which can be shown to give equivalent or superior results to those specified.

1.3 NORMATIVE REFERENCES

The following documents are referred to in this Standard.

A	AS	
1	180	Methods of test for hose made from elastomeric materials
1	391	Methods for tensile testing of metals
1	554	Structural steel welding (all parts)
1	665	Welding of aluminium structures
1	815	Metallic materials—Rockwell hardness test
1	816	Metallic materials—Brinell hardness test
1	817	Metallic materials—Vickers hardness test
2	019	Fluid power—Hydraulic and pneumatic cylinders—Bore and rod dimensions
2	074	Cast steels
2	2321	Short-link chains for lifting purposes

© Standards Australia



This is a free preview. Purchase the entire publication at the link below:

AS 5047: 2005: EN: COMBINED PDF

- Dooking for additional Standards? Visit SAI Global Infostore
- (>) Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation