

Australian Standard[®]

**Surface roughness comparison
specimens**

The following scientific, industrial and governmental organizations and departments were officially represented on the committee entrusted with the preparation of this standard:

Confederation of Australian Industry
CSIRO, Division of Applied Physics
CSIRO, Division of Mechanical Engineering
Department of Defence
Department of Industry and Commerce
Department of Technical and Further Education
Federal Chamber of Automotive Industries
Institute of Technology, South Australia
Institution of Engineers Australia
Institution of Production Engineers
Metal Trades Industry Association of Australia
Railways of Australia Committee
Society of Manufacturing Engineers
University of New South Wales
University of Queensland

This standard, prepared by Committee ME/27, Limits and Fits and Metrology, was approved on behalf of the Council of the Standards Association of Australia, on 15 December 1980, and was published on 1 April 1981.

Review of Australian Standards. *To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This standard was issued in draft form for comment as DR 79195.

Australian Standard[®]

**Surface roughness comparison
specimens**

First published	1981
Reconfirmed	1987

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 2191 0

PREFACE

This standard was prepared by the Association's Committee on Limits and Fits and Metrology as part of its program to prepare a rational selection of metrology standards in metric units.

The need for a standard arises because of the widespread use of tactile and visual methods of assessing surface roughness in industry generally. Such methods require the use of standardized surface roughness comparison specimens.

In preparing this standard, the committee fully took into account the relevant ISO standards, and the standard is based on and is technically equivalent to the following documents:

- ISO 2632/1 Roughness Comparison Specimens—Part I: Turned, Ground, Bored, Milled, Shaped and Planed
- ISO 2632/2 Roughness Comparison Specimens—Part II: Spark-eroded, Shot Blasted and Grit Blasted, and Polished
- ISO 2632/3 Roughness Comparison Specimens—Part III: Cast Surfaces

The standard covers individually machined (or cast) specimens, but with the developments which have taken place in the electroforming of specimens, it is the latter form which is most commonly used in industry. The electroformed high fidelity specimens can be reproduced from a single master surface thus reducing the problems of achieving and maintaining compatibility between specimens. Reference is also made to plastics specimens which may have particular merits in the assessment of non-metallic parts.

Surface roughness can be assessed by actual measurement (see AS 1965) or by tactile and visual comparison with reference specimens referring to the same machining or casting process. For the latter purpose, sets of reference specimens are widely used in workshop and inspection departments.

This standard may require reference to the following publications:

- AS 1100 Drawing Practice
Part 2—Abbreviations and Symbols
- AS 1965 The Measurement of Surface Roughness with Direct-reading Stylus Electronic Instruments
- SAA MP19 Report on Preferred Numbers and Their Use
- AS Surface Texture*

* In course of preparation.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SECTION 1. SCOPE AND GENERAL REQUIREMENTS	
1.1 Scope	4
1.2 Definitions	4
1.3 Methods of Manufacture	4
1.4 Surface Characteristics	4
1.5 Flaws	4
1.6 Size of Surface Roughness Specimens	4
1.7 Marking	4
SECTION 2. TURNED, GROUND, BORED, MILLED, SHAPED, AND PLANED SPECIMENS	
2.1 Scope of Section	6
2.2 Tolerance Values	6
2.3 Cut-off Lengths	6
2.4 Lay	6
SECTION 3. SPARK-ERODED, SHOT BLASTED, GRIT BLASTED, AND POLISHED SPECIMENS	
3.1 Scope of Section	8
3.2 Tolerance Values	8
3.3 Cut-off Lengths	8
3.4 Lay	8
SECTION 4. ROUGHNESS COMPARISON SPECIMENS FOR CAST SURFACES	
4.1 Scope of Section	10
4.2 Tolerance Values	10
4.3 Cut-off Lengths	10
SECTION 5. CALIBRATION	
5.1 Scope of Section	12
5.2 Evaluation	12
APPENDICES	
A Typical Sets of Mounted Roughness Comparison Specimens	13
B Use of Roughness Comparison Specimens	14
C Values of R_a	15

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard
for
SURFACE ROUGHNESS COMPARISON SPECIMENS

SECTION 1. SCOPE AND GENERAL REQUIREMENTS

1.1 SCOPE. This standard specifies the characteristics of surface roughness comparison specimens intended for tactile and visual comparison with workpiece surfaces produced by similar processes. Roughness comparison specimens for the following processes are given:

- (a) Turned, ground, bored, milled, shaped or planed specimens: (Section 2).
- (b) Spark-eroded, shot blasted, grit blasted, or polished specimens: (Section 3).
- (c) Specimens for cast surfaces: (Section 4).
- (d) Calibration of surface roughness specimens: (Section 5).

The standard also includes definitions used in surface roughness and gives information on cut-off lengths and marking requirements. Appendices give information on typical sets of mounted roughness comparison specimens, the use of roughness comparison specimens, roughness grade numbers and roughness average values of R_a (arithmetic mean deviation) in both metric and the corresponding imperial units.

1.2 DEFINITIONS. For the purpose of this standard, the following definitions apply:

NOTE: For other terms and definitions, see AS*

1.2.1 Surface roughness comparison specimen—a specimen surface of known average roughness height (R_a) representing a particular casting, machining or other production process. The specimen is used to give design and workshop personnel guidance on the feel and appearance of the particular production process and surface grade to enable visual and tactile evaluation of the production surface.

1.2.2 Surface roughness—the topography of a surface which consists of short wavelengths only.

1.2.3 Arithmetic mean deviation (R_a)—the arithmetic average of the deviation of a profile above and below the reference curve or line. This parameter has the dimensions of length.

1.2.4 Measuring traverse length (evaluation length)—the length of the modified profile used in measurement of surface roughness parameters. It may contain one or more cut-off lengths.

1.2.5 Cut-off (λ_B)—the value of the wavelength (λ) defined by convention as the longest wave length transmitted by the instrument.

NOTE: The transmission cut-off corresponds in concept with the sampling length which is often used in geometric definitions of roughness parameters. Cut-off and sampling length are numerically equal.

1.2.6 Lay—the direction of the predominant surface pattern ordinarily determined by the production method used.

1.2.7 Flaws—unintentional irregularities which occur at one place, or at relatively infrequent or widely varying intervals on the surface.

NOTE: Flaws include such defects as cracks, blow holes, inclusions, ridges, scratches, etc.

1.3 METHODS OF MANUFACTURE. Surface roughness comparison specimens are normally manufactured as follows:

- (a) By electroforming positive replicas of master surfaces.
- (b) By making positive replicas in plastics materials of master surfaces, and by coating or otherwise, so that the feel and appearance of the natural cast or manufactured surface should be represented.
- (c) By direct application of the production process which the specimen is intended to represent, i.e. individual machined specimens.

1.4 SURFACE CHARACTERISTICS. Electroformed and plastics replicas reproduced from master surfaces, or individually machined specimens, shall exhibit only the characteristics resulting from the natural action of the casting or production process which they are intended to represent. For cast surfaces this shall also include any shot blasting, grit blasting, or any other appropriate cleaning treatment. They shall not contain other surface irregularities such as can be induced by abnormal conditions.

1.5 FLAWS. The effect of flaws shall not be included in the roughness measurement. Where flaws are to be restricted or controlled, a special note as to the method of inspection should be included on the drawing or specification.

1.6 SIZE OF SURFACE ROUGHNESS SPECIMENS. Surface roughness comparison specimens shall be of a size adequate to permit initial and periodic calibration. The minimum lengths of the longer sides shall be—

- (a) for R_a values of 0.2 μm to 6.3 μm . . . 20 mm;
- (b) for the R_a value 12.5 μm 30 mm;
- (c) for R_a values 25 μm and above 50 mm.

1.7 MARKING. Each surface roughness specimen, or its mounting, shall be marked with the following information, which shall not be applied to the reference surface of the specimen:

- (a) Specimens for cast surfaces.
 - (i) The manufacturer's trade (identification) mark together with the roughness number, where applicable (see Table 1.1).

* AS, Surface Texture (in course of preparation).

This is a free preview. Purchase the entire publication at the link below:

AS 2382 : 1981 : EN : COMBINED PDF

-
- ⊙ Looking for additional Standards? Visit SAI Global Infostore
 - ⊙ Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-

Need to speak with a Customer Service Representative - Contact Us