

Australian/New Zealand Standard™

**Timber—Bond performance of structural adhesives**



## **AS/NZS 4364:2010**

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee TM-004, Glued Laminated Timber Products. It was approved on behalf of the Council of Standards Australia on 27 October 2010 and on behalf of the Council of Standards New Zealand on 29 October 2010. This Standard was published on 1 December 2010.

---

The following are represented on Committee TM-004:

A3P  
BRANZ  
CSIRO  
Decorative Wood Veneers Association  
Engineered Wood Products Association of Australasia  
Forest Industries Association of Tasmania  
Forests New South Wales  
Glued Laminated Timber Association of Australia  
Institution of Professional Engineers New Zealand  
Monash University  
New Zealand Pine Manufacturers Association  
New Zealand Timber Industry Federation  
Scion  
Structural Engineered Timber Manufacturers Association  
Timber Queensland

Additional Interests:

Prof Bob Milner

---

### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at [www.saiglobal.com.au](http://www.saiglobal.com.au) or Standards New Zealand web site at [www.standards.co.nz](http://www.standards.co.nz) and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

---

*This Standard was issued in draft form for comment as DR AS/NZS 4364.*

---

## Australian/New Zealand Standard™

# Timber—Bond performance of structural adhesives

First published as AS/NZS 4364:1996.  
Interim revision 2007.  
AS/NZS 4364:1996 and AS/NZS 4364(Int):2007 revised and designated as AS/NZS 4364:2010.

### **COPYRIGHT**

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140

ISBN 978 0 7337 9735 4

## PREFACE

This Australian/New Zealand Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee TM-004, Glued Laminated Timber Products, to supersede AS/NZS 4364:1996, *Adhesives, phenolic and aminoplastic for load-bearing timber structures—Classification and performance requirements*, and AS/NZS 4364(Int):2007.

The objective of this Australian/New Zealand Standard is to provide requirements for bond performance of adhesives formed in structural finger-jointed timber and glulam products. It is largely based on the Canadian Standards Association document CSA O112.9, *Evaluation of adhesives for structural wood products (exterior exposure)*. Alternative requirements, taken from the European Standards, are also included.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the appendix to which they apply. A ‘normative’ appendix is an integral part of a Standard, whereas an ‘informative’ appendix is only for information and guidance.

Statements expressed in mandatory terms in notes to tables and figures are deemed to be requirements of this Standard.

## CONTENTS

	<i>Page</i>
FOREWORD.....	4
1 SCOPE.....	5
2 APPLICATION .....	5
3 NORMATIVE REFERENCES .....	5
4 DEFINITIONS.....	6
5 NOTATION.....	6
6 REQUIREMENTS.....	7
6.1 Classification and specification.....	7
6.2 Adhesive formulation and application.....	7
6.3 Fillers and extenders .....	7
6.4 Anti-fungal properties.....	7
6.5 pH of cured adhesive film .....	7
6.6 Shear strength and wood failure.....	8
6.7 Delamination resistance .....	9
6.8 Creep resistance .....	9
7 SAMPLE PREPARATION AND TEST METHODS.....	10
7.1 Anti-fungal properties.....	10
7.2 pH of cured adhesive film .....	10
7.3 Wood species and density .....	10
7.4 Wood moisture content .....	11
7.5 Shear test and wood failure assessment.....	11
7.6 Delamination resistance test.....	16
7.7 Creep resistance test.....	20
8 REPORT .....	28
8.1 General .....	28
8.2 Product details .....	28
8.3 Specimen preparation and testing.....	28
8.4 Test results.....	29
 APPENDICES	
A MEASUREMENT AND COMPUTATION OF BONDLINE CREEP FOR ENVIRONMENTS A, B AND C.....	30
B INTERRUPTING THE BOIL-DRY-FREEZE CONDITIONING .....	31
C EXAMPLE OF CALCULATING TOTAL DELAMINATION WITHIN AN INDIVIDUAL BONDLINE.....	32
BIBLIOGRAPHY .....	34

## FOREWORD

This Australian/New Zealand Standard focuses on bondline performance and is directed principally at the evaluation of wood adhesives. When used in this manner the tests and assessments are made against standardized wood species. It is expected that product Standards (e.g., for glulam, laminated veneer lumber, etc.) would insist that selected requirements be met in the establishment of a new production line or the introduction of a new product, new adhesive, new species, etc., on an existing production line as part of qualification procedures.

## STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

**Australian/New Zealand Standard****Timber—Bond performance of structural adhesives****1 SCOPE**

This Australian/New Zealand Standard specifies performance requirements for adhesives according to their suitability for use in prefabricated timber components for structural use in defined environmental conditions and for such adhesives for the manufacture of structural finger-jointed timber and glulam.

NOTE: This Australian/New Zealand Standard does not cover the performance requirements for adhesive bonds between structural timber components in plywood, LVL, and wood-based panel products; however, the adhesive bond requirements may be applicable to these products.

**2 APPLICATION**

This Australian/New Zealand Standard is intended to be used primarily by adhesive manufacturers.

The requirements of the adhesive bond are based on the performance of the adhesive as measured by the following properties:

- (a) Resistance to biological degradation .....Clause 6.4.
- (b) pH of cured adhesive film .....Clause 6.5.
- (c) Resistance to shear in the dry and wet states by compression loading .....Clause 6.6.
- (d) Hydro-mechanical response or resistance to delamination during exposure to wetting and drying .....Clause 6.7.
- (e) Resistance to creep under static shear loading during exposure to high humidity, heat and combined heat and moisture .....Clause 6.8.

Either Method A or Method B shall be chosen for testing resistance to shear, resistance to delamination, and resistance to creep (Section 7). There shall be no mixing of Methods A and B (for example, Method A for shear resistance and Method B for delamination) nor shall retesting of the same adhesive be permitted once the choice of the test method family (A or B) is made.

## NOTES:

- 1 In the case of resistance to shear in the dry and wet states, resistance to delamination during exposure to wetting and drying, and resistance to creep static shear loading during exposure to high humidity, heat and combined heat and moisture, two alternative requirements are provided. Method A is based on CSA O112.9 and Method B is based on EN test methods (see Clause 3).
- 2 The current product Standards refer to Type I and II adhesives, which prescribe requirements for use in Service Classes 1, 2, 3, as defined in Table 6.1.1.

**3 NORMATIVE REFERENCES**

The following are the normative documents referenced in this Standard:

## AS/NZS

1080 Timber—Methods of test

1080.1 Method 1: Moisture content

1080.3 Method 3: Density

4491 Timber—Glossary of terms in timber-related Standards

This is a free preview. Purchase the entire publication at the link below:

**AS/NZS 4364 : 2010 : EN : COMBINED PDF**

- 
- ⏪ Looking for additional Standards? Visit SAI Global Infostore
  - ⏩ Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
- 

Need to speak with a Customer Service Representative - Contact Us