

AS 3008.1—1989
1998 ed FWD 971117

SE BY AS/NZS 3008.1.1-1993
(TAS FEB 1993)

(WITHDRAWN TAS
MARCH 1993)

Australian Standard®

**Electrical installations—Selection of
cables**

**Part 1: Cables for alternating
voltages up to and including
0.6/1 kV**

STANDARDS AUSTRALIA
✓

This Australian Standard was prepared by Committee EL/1, Wiring Rules. It was approved on behalf of the Council of Standards Australia on 18 May 1989 and published on 15 September 1989.

The following interests are represented on Committee EL/1:

- Association of Consulting Engineers, Australia
- Australian Consumers Association
- Australian Electrical and Electronic Manufacturers Association
- Confederation of Australian Industry
- Department of Housing and Construction
- Electrical Contractors Associations of Australia
- Electrical regulatory authorities
- Electrical Trades Union of Australia
- Electricity Supply Association of Australia
- Institute of Electrical Inspectors
- Institution of Engineers, Australia
- Insurance Council of Australia
- Telecom Australia

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

AS 3008.1—1989

Australian Standard®

**Electrical installations—Selection of
cables**

**Part 1: Cables for alternating
voltages up to and including
0.6/1 kV**

First published as AS 3008.1—1984.
Second edition 1989.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 5797 4

PREFACE

This Standard was prepared by the Standards Australia Committee on Wiring Rules to supersede AS 3008.1—1984. It is Part 1 of a two-part Standard, this part dealing with cables for use with alternating voltages up to and including 0.6/1kV. Part 2 (in course of preparation) will deal with cables for use with alternating voltages over 1 kV.

The preparation of this edition was undertaken to incorporate into the Standard Amendment No 1 to AS 3008.1—1984 and to effect the following changes to that edition—

- (a) Table 1 deleted. Therefore the numbers of all tables have been altered accordingly (including those referenced below).
- (b) Clauses 3.4 and 3.5 and Tables 3 to 10 with regard to installation of cables partially or completely surrounded by thermal insulation.
- (c) Tables 11 and 12 amended to delete reference to number and diameter of wires and a reference to AS 1125 inserted.
- (d) Tables 18 and 19 have been extended to include current capacities for neutral screened cables. Values for XLPE insulated aluminium cables have been added to Table 19.
- (e) Table 57 has been amended and extended to provide values down to a temperature of 25°C.
- (f) Other changes include definitions for ladder support and perforated tray and a number of explanatory notes.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the Head Office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
FOREWORD	7
1. SCOPE AND GENERAL	
1.1 SCOPE	8
1.2 ALTERNATIVE SPECIFICATIONS	8
1.3 REFERENCED AND RELATED DOCUMENTS	8
1.4 DEFINITIONS	9
2. CABLE SELECTION PROCEDURE	
2.1 GENERAL	9
2.2 SELECTION PROCESS	9
2.3 DETERMINATION OF MINIMUM CABLE SIZE BASED ON CURRENT-CARRYING CAPACITY CONSIDERATIONS	9
2.4 DETERMINATION OF MINIMUM CABLE SIZE BASED ON VOLTAGE DROP CONSIDERATIONS	10
2.5 DETERMINATION OF MINIMUM CABLE SIZE BASED ON THE SHORT-CIRCUIT TEMPERATURE CONSIDERATIONS	10
3. CURRENT-CARRYING CAPACITY	
3.1 GENERAL	10
3.2 TYPES OF CONDUCTORS	10
3.3 TYPES OF CABLE	10
3.4 INSTALLATION CONDITIONS	12
3.5 EXTERNAL INFLUENCES ON CABLES	13
4. VOLTAGE DROP	
4.1 GENERAL	43
4.2 DETERMINATION OF VOLTAGE DROP FROM MILLIVOLTS PER AMPERE METRE	43
4.3 DETERMINATION OF VOLTAGE DROP FROM CIRCUIT IMPEDANCE	43
4.4 DETERMINATION OF VOLTAGE DROP FROM CABLE OPERATING TEMPERATURE	44
4.5 DETERMINATION OF VOLTAGE DROP FROM LOAD POWER FACTOR	44
4.6 DETERMINATION OF VOLTAGE DROP IN UNBALANCED MULTIPHASE CIRCUITS	45
5. SHORT-CIRCUIT PERFORMANCE	
5.1 GENERAL	60
5.2 FACTORS GOVERNING THE APPLICATION OF THE TEM- PERATURE LIMITS	60
5.3 CALCULATION OF PERMISSIBLE SHORT-CIRCUIT CURRENTS	60
5.4 INFLUENCE OF METHOD OF INSTALLATION	61
5.5 MAXIMUM PERMISSIBLE SHORT CIRCUIT TEMPERATURES	61
APPENDICES	
A RECOMMENDED CIRCUIT CONFIGURATIONS FOR THE INSTALLATION OF SINGLE-CORE CABLES IN PARALLEL	62
B EXAMPLES ON THE SELECTION OF CABLES TO SATISFY CURRENT-CARRYING CAPACITY, VOLTAGE DROP AND SHORT-CIRCUIT PERFORMANCE REQUIREMENTS	63

LIST OF TABLES

1	LIMITING TEMPERATURES FOR INSULATED CABLES	11
2	SCHEDULE OF INSTALLATION METHODS FOR CABLES DEEMED TO HAVE THE SAME CURRENT-CARRYING CAPA- CITY AND CROSS-REFERENCES TO APPLICABLE DERATING TABLES	18
3	CURRENT-CARRYING CAPACITIES OF TWO SINGLE-CORE 0.6/1 kV SHEATHED AND UNSHEATHED NON-ARMOURED CABLES WITH R75, V75, V90 OR V105 INSULATION	22
4	CURRENT-CARRYING CAPACITIES OF TWO SINGLE-CORE 0.6/1 kV SHEATHED AND UNSHEATHED NON-ARMOURED CABLES WITH XLPE, R-EP-90 OR R-CSP-90 INSULATION	23
5	CURRENT-CARRYING CAPACITIES OF THREE SINGLE-CORE 0.6/1 kV SHEATHED AND UNSHEATHED NON-ARMOURED CABLES WITH R75, V75, V90 OR V105 INSULATION	24
6	CURRENT-CARRYING CAPACITIES OF THREE SINGLE-CORE 0.6/1 kV SHEATHED AND UNSHEATHED NON-ARMOURED CABLES WITH XLPE, R-EP-90 OR R-CSP-90 INSULATION	25
7	CURRENT-CARRYING CAPACITIES OF TWO-CORE 0.6/1 kV INSULATED AND SHEATHED (INCLUDING NEUTRAL SCREENED) CABLES WITH OR WITHOUT EARTH CONDUCT- TOR, ARMOURED OR NON-ARMOURED WITH R75, V75 OR V90 INSULATION	26
8	CURRENT-CARRYING CAPACITIES OF TWO-CORE 0.6/1 kV INSULATED AND SHEATHED (INCLUDING NEUTRAL SCREENED) CABLES WITH OR WITHOUT EARTH CONDUCT- TOR, ARMOURED OR NON-ARMOURED WITH XLPE, R-EP-90 OR R-CSP-90 INSULATION	27
9	CURRENT-CARRYING CAPACITIES OF THREE-CORE AND FOUR-CORE 0.6/1 kV INSULATED AND SHEATHED (INCLU- DING NEUTRAL SCREENED) CABLES WITH OR WITHOUT EARTH CONDUCTOR, ARMOURED OR NON-ARMOURED WITH V75, V90 OR V105 INSULATION	28
10	CURRENT-CARRYING CAPACITIES OF THREE-CORE AND FOUR-CORE 0.6/1 kV INSULATED AND SHEATHED (INCLU- DING NEUTRAL SCREENED) CABLES WITH OR WITHOUT EARTH CONDUCTOR, ARMOURED OR NON-ARMOURED WITH XLPE, R-EP-90 OR R-CSP-90 INSULATION	29
11	CURRENT-CARRYING CAPACITIES OF 0.6/1 kV FLEXIBLE CABLES	30
12	CURRENT-CARRYING CAPACITIES OF FLEXIBLE CORDS	30
13	CURRENT-CARRYING CAPACITIES OF CABLES AND FLEXIBLE CORDS WITH R-S-150, TYPE 150 FIBROUS OR 150 TYPE PTFE INSULATION	31
14	CURRENT-CARRYING CAPACITIES OF MINERAL-INSULATED COPPER-SHEATHED CABLES WITH COPPER CONDUCTORS	32
15	CURRENT-CARRYING CAPACITIES OF 1/1 kV MINERAL- INSULATED ALUMINIUM-SHEATHED PVC-SERVED CABLES WITH ALUMINIUM CONDUCTORS	32
16	CURRENT-CARRYING CAPACITIES FOR SINGLE-CORE 0.6/1 kV PAPER-INSULATED LEAD-SHEATHED CABLES, TREFOIL FORMATION	33
17	CURRENT-CARRYING CAPACITIES FOR THREE-CORE AND FOUR-CORE 0.6/1 kV PAPER-INSULATED LEAD-SHEATHED AND ARMOURED OR ALUMINIUM-SHEATHED CABLES	33
18	CURRENT-CARRYING CAPACITIES OF AERIAL CABLES WITH COPPER CONDUCTORS	34
19	CURRENT-CARRYING CAPACITIES OF AERIAL CABLES WITH ALUMINIUM CONDUCTORS	35
20	DERATING FACTORS FOR BUNCHED CIRCUITS OF SINGLE- CORE OR MULTICORE CABLES IN AIR OR IN CONDUIT OR SIMILAR WIRING ENCLOSURES	36

	<i>Page</i>
21 DERATING FACTORS FOR CIRCUITS OF SINGLE-CORE CABLES INSTALLED ON TRAYS, RACKS, CLEATS, OR OTHER SUPPORTS IN AIR	37
22 DERATING FACTORS FOR CIRCUITS OF MULTICORE CABLES INSTALLED ON TRAYS, RACKS, CLEATS OR OTHER SUPPORTS IN AIR	38
23 DERATING FACTORS FOR GROUPS OF CIRCUITS OF SINGLE-CORE OR MULTICORE CABLES INSTALLED DIRECTLY IN THE GROUND	39
24 DERATING FACTORS FOR GROUPS OF CIRCUITS OF SINGLE-CORE OR MULTICORE CABLES IN INSTALLED UNDERGROUND CONDUITS, PIPES OR DUCTS	40
25 RATING FACTORS FOR VARIATIONS IN AMBIENT TEMPERATURE FOR CABLES IN AIR OR HEATED CONCRETE SLABS, AND FOR CABLES BURIED DIRECT IN GROUND OR IN UNDERGROUND DUCTS	41
26 RATING FACTORS FOR VARIATIONS IN DEPTH OF LAYING FOR CABLES BURIED DIRECT IN THE GROUND AND FOR CABLES INSTALLED IN UNDERGROUND CONDUITS, PIPES OR DUCTS	42
27 RATING FACTORS FOR CABLES BURIED DIRECT IN GROUND AND FOR CABLES INSTALLED IN UNDERGROUND ENCLOSURES WHERE THE THERMAL RESISTIVITY OF THE SOIL VARIES FROM 1.2°C.m/W	42
28 REACTANCE AT 50 Hz OF ALL CABLES EXCLUDING FLEXIBLE CORDS AND CABLES, MINERAL-INSULATED METAL-SHEATHED CABLES, PAPER-INSULATED CABLES AND AERIAL CONDUCTORS	46
29 REACTANCE AT 50 Hz OF FLEXIBLE CORDS AND CABLES	46
30 REACTANCE AT 50 Hz OF MINERAL-INSULATED METAL-SHEATHED CABLES	47
31 REACTANCE AT 50 Hz OF PAPER-INSULATED LEAD-SHEATHED CABLES	47
32 REACTANCE AT 50 Hz OF SINGLE-CORE AERIAL CONDUCTORS WITH BARE OR INSULATED CONDUCTORS	48
33 A.C. RESISTANCE AT 50 Hz OF SINGLE-CORE CABLES	48
34 A.C. RESISTANCE AT 50 Hz OF MULTICORE CABLES WITH CIRCULAR CONDUCTORS	49
35 A.C. RESISTANCE AT 50 Hz OF MULTICORE CABLES WITH SHAPED CONDUCTORS	49
36 A.C. RESISTANCE AT 50 Hz OF FLEXIBLE CABLES AND CORDS WITH COPPER CONDUCTORS	50
37 A.C. RESISTANCE AT 50 Hz OF MINERAL-INSULATED METAL-SHEATHED CABLES	50
38 A.C. RESISTANCE AT 50 Hz OF SINGLE-CORE AERIAL CABLES WITH BARE OR INSULATED CONDUCTORS	51
39 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE INSULATED AND SHEATHED COPPER CONDUCTORS, LAID IN TREFOIL	51
40 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE INSULATED AND SHEATHED COPPER CONDUCTORS, LAID FLAT TOUCHING	52
41 THREE-PHASE VOLTAGE DROP AT 50 Hz OF MULTICORE CABLES WITH CIRCULAR COPPER CONDUCTORS	52
42 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE INSULATED AND SHEATHED TINNED COPPER CONDUCTORS, LAID IN TREFOIL	53
43 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE INSULATED AND SHEATHED TINNED COPPER CONDUCTORS, LAID FLAT TOUCHING	53
44 THREE-PHASE VOLTAGE DROP AT 50 Hz OF MULTICORE CABLES WITH CIRCULAR TINNED COPPER CONDUCTORS	54

	<i>Page</i>
45 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE INSULATED AND SHEATHED ALUMINIUM CONDUCTORS, LAID IN TREFOIL	54
46 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE INSULATED AND SHEATHED ALUMINIUM CONDUCTORS, LAID FLAT TOUCHING	55
47 THREE-PHASE VOLTAGE DROP AT 50 Hz OF MULTICORE CABLE WITH CIRCULAR ALUMINIUM CONDUCTORS	55
48 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE FLEXIBLE CABLES AND CORDS WITH COPPER CONDUCTORS, LAID IN TREFOIL	56
49 THREE-PHASE VOLTAGE DROP AT 50 Hz OF MULTICORE FLEXIBLE CABLES AND CORDS WITH COPPER CONDUCTORS	56
50 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE AND MULTI-CORE MINERAL-INSULATED METAL-SHEATHED (MIMS) CABLES, LAID IN TREFOIL	57
51 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE PAPER-INSULATED CABLE WITH COPPER CONDUCTORS, LAID IN TREFOIL	57
52 THREE-PHASE VOLTAGE DROP AT 50 Hz OF SINGLE-CORE PAPER-INSULATED CABLES WITH ALUMINIUM CONDUCTORS, LAID IN TREFOIL	58
53 THREE-PHASE VOLTAGE DROP AT 50 Hz OF MULTICORE PAPER-INSULATED CABLE WITH COPPER CONDUCTORS	58
54 THREE-PHASE VOLTAGE DROP AT 50 Hz OF MULTICORE PAPER-INSULATED CABLE WITH ALUMINIUM CONDUCTORS	58
55 THREE-PHASE VOLTAGE DROP AT 50 Hz OF AERIAL CABLES WITH BARE OR INSULATED COPPER CONDUCTORS	59
56 THREE-PHASE VOLTAGE DROP AT 50 Hz OF AERIAL CABLES WITH BARE OR INSULATED ALUMINIUM CONDUCTORS	59
57 VALUES OF CONSTANT <i>K</i> FOR DETERMINATION OF PERMISSIBLE SHORT-CIRCUIT CURRENTS	60
58 TEMPERATURE LIMITS FOR INSULATING MATERIALS IN CONTACT WITH CONDUCTORS	61
59 TEMPERATURE LIMITS FOR OUTER SHEATH AND BEDDING MATERIALS	61
60 TEMPERATURE LIMITS FOR CONDUCTOR AND METALLIC SHEATH MATERIALS AND COMPONENTS	61

FOREWORD

This Standard gives the sustained or continuous constant current which is sufficient to produce the maximum permissible cable temperature under specified ambient conditions. The time taken to reach this steady state temperature will vary depending on the type of cable and installation conditions. There will be many cable installations where, because of cable selection practices or demand patterns, the current is not sustained at the maximum specified in this Standard. Under these conditions care should be taken in the application of the correction factors included in Tables 20 to 24; it may be possible to derive other appropriate correction factors for these installations.

The contents of the Standard are a development of the limited provision of Appendix B to AS 3000 and it is expected that over subsequent revisions of AS 3000, Appendix B will be modified and reduced in size and reference made to this Standard.

STANDARDS AUSTRALIA

Australian Standard
Electrical installations—Selection of cables

Part 1: Cables for alternating voltages up to and including 0.6/1kV

1. SCOPE AND GENERAL

1.1 SCOPE. This Standard sets out a method for cable selection for those types of electrical cables and methods of installation which are in common use at working voltages up to and including 0.6/1 kV a.c.

Three criteria are given for cable selection as follows:

- (a) Current-carrying capacity.
- (b) Voltage-drop.
- (c) Short-circuit temperature rise.

This Standard provides sustained current-carrying capacities and voltage drop values for those types of electrical cable and installation practices in common use in Australia. A significant amount of explanatory material is also provided on the application of rating factors which arise from the particular installation conditions of a single circuit or groups of circuits. Also provided in Clause 5 is information on cable selection based on short-circuit temperature limits.

NOTE: A number of worked examples on cable selection are included in Appendix B.

This Standard does not take into account the effects that may occur owing to temperature rise at the terminals of equipment and reference is necessary to AS 3000 and the individual equipment Standards.

1.2 ALTERNATIVE SPECIFICATIONS. AS 3000 gives current-carrying capacities for a limited number of cable installation conditions. These conditions are included in this Standard but, in some cases where recalculations have been performed, the tabulated values differ slightly between the Standards. Where this occurs the current-carrying capacity given in this Standard is considered to be more accurate but either value is acceptable for the application of any appropriate requirements of AS 3000, e.g. maximum current rating of a circuit-protective device.

Where the type of cable or method of installation is not specifically covered in the tables of this Standard, current-carrying capacities obtained from alternative specifications such as ERA Report 69-30, may be employed.

ERA Report 69-30, particularly Part III, gives information on the following areas which are not covered by this Standard:

- (a) The d.c. current-carrying capacities of two single-core cables and one two-core cable.
- (b) The current-carrying capacity of armoured single-core cables.
- (c) Group rating factors for underground cables laid in tier formation.

Current-carrying capacities may also be determined by calculation using IEC 287 and appropriate cable data. The subject of assigning a current-carrying capacity to a cyclically or intermittently loaded cable is not covered

in this Standard. However reference may be made to ERA Report F/T I86 for information on the determination of such cable ratings by calculation.

1.3 REFERENCED AND RELATED DOCUMENTS.

1.3.1 Referenced documents. The following documents are referred to in this Standard:

STANDARDS

- | | |
|------|---|
| AS | |
| I125 | Conductors in insulated cables and flexible cords (metric units) |
| 3000 | SAA Wiring Rules |
| IEC | |
| 287 | Calculation of the continuous current ratings of cables (100 percent load factor) |

APPROVAL AND TEST SPECIFICATIONS

- | | |
|------|---|
| AS | |
| 3100 | Definitions and general requirements for electrical materials and equipment |
| 3191 | Electric flexible cords |
| 3300 | General requirements for household and similar electrical appliances |

ERA REPORTS*

- | | |
|----------|--|
| 69-30 | Current rating standards for distribution cables |
| Part I | Sustained current ratings for paper-insulated lead-sheathed cables |
| Part II | Sustained current ratings for paper-insulated cables with aluminium sheath/neutral conductor and three shaped solid aluminium phase conductors |
| Part III | Sustained current ratings for PVC-insulated cables |
| Part V | Sustained current ratings for armoured cables with thermosetting insulation |
| F/T I86 | Methods for the calculation of cyclic rating factors and emergency loading for cables laid direct in the ground or in ducts |

1.3.2 Related documents. The following documents are related to this Standard:

APPROVAL AND TEST SPECIFICATIONS

- | | |
|------|--|
| AS | |
| 3116 | Elastomer insulated electric cables and flexible cables for working voltages of 0.6/1 kV |
| 3147 | PVC insulated electric cables and flexible cables for working voltages of 0.6/1 kV |

* ERA = Reports from ERA Technology Ltd (UK).

This is a free preview. Purchase the entire publication at the link below:

AS 3008.1 : 1989 : EN : COMBINED PDF

-
- ⤵ Looking for additional Standards? Visit SAI Global Infostore
 - ⤵ Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-

Need to speak with a Customer Service Representative - Contact Us