

Australian Standard[®]

Mobile waste containers

Part 2: Containers with four wheels with a capacity from 500 L to 1200 L with flat lid(s), for trunnion and/or lifting devices—Dimensions and design



This Australian Standard® was prepared by Committee PL 047, Mobile waste containers. It was approved on behalf of the Council of Standards Australia on 23 May 2008. This Standard was published on 30 June 2008.

The following are represented on Committee PL 047:

- Department of Environment and Climate Change, NSW
 - Plastics and Chemicals Industries Association
 - Sustainability Victoria
 - Victorian Waste Management Association
 - Waste Contractors and Recyclers Association of NSW
 - Waste Management Association of Australia
-

This Standard was issued in draft form for comment as DR 05346.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

Mobile waste containers

Part 2: Containers with four wheels with a capacity from 500 L to 1200 L with flat lid(s), for trunnion and/or lifting devices—Dimensions and design

First published as AS 4123.2—2008.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7337 8818 1

PREFACE

This Standard was prepared by Committee PL-047, Mobile Waste Containers.

The objective of this Standard is to provide manufacturers, designers and regulatory authorities with uniform minimum requirements for the safety and performance of mobile waste containers. This does not include front lift, mini skips or other material handling bins.

This Standard is part of a series of Standards on mobile waste containers which when complete will consist of the following:

AS

4123	Mobile waste containers
4123.1	Part 1: Containers with two wheels with a capacity up to 400 L for lifting devices—Dimensions and design
4123.2	Part 2: Containers with four wheels with a capacity from 500 L to 1200 L with flat lid(s), for trunnion and/or lifting devices—Dimensions and design (this Standard)
4123.3	Part 3: Containers with four wheels with a capacity from 770 L to 1300 L with dome lid(s), for trunnion and/or lifting devices—Dimensions and design
4123.4	Part 4: Containers with four wheels with a capacity from 750 L to 1700 L with flat lid(s), for wide trunnion or BG and/or wide comb lifting devices—Dimensions and design
4123.5	Part 5: Performance requirements and test methods
4123.6	Part 6: Health, safety and environment
4123.7	Part 7: Colours, markings, and designation requirements

No consideration was given to the lifting systems other than those specified.

This Standard should not be regarded as a design specification or as an instruction manual.

In the preparation of this Standard, consideration has been given to—

- (a) continuity of satisfactory operation;
- (b) the prevention of injury to persons or property;
- (c) encouraging the use of recycled material in the manufacture;
- (d) consistency of colours for mobile waste containers; and
- (e) relevant international Standards.

The terms ‘normative’ and ‘informative’ are used to define the application of the appendix to which they apply. A normative appendix is an integral part of a Standard, whereas an informative appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
1 SCOPE.....	4
2 REFERENCED DOCUMENTS.....	4
3 DEFINITIONS.....	4
4 VOLUMES	5
5 DIMENSIONS AND DESIGN	5
6 NOMINAL LOAD.....	6
7 TESTING.....	6
8 HEALTH, SAFETY AND ENVIRONMENT REQUIREMENTS	6
9 COLOURS, MARKINGS AND DESIGNATIONS	6
APPENDIX A RECOMMENDATIONS FOR MANUFACTURERS OF LIFTING DEVICES.....	16

STANDARDS AUSTRALIA

Australian Standard
Mobile waste containers

Part 2: Containers with four wheels with a capacity from 500 L to 1200 L with flat lid(s), for trunnion and/or lifting devices—Dimensions and design

1 SCOPE

This Standard specifies dimensions and design requirements for mobile waste containers with four wheels, with flat lid(s) and capacity from 500 L to 1200 L to be used by trunnion and/or comb lifting devices.

2 REFERENCED DOCUMENTS

The following documents are referenced in this Standard.

AS

4123	Mobile waste containers
4123.1	Part 1: Containers with two wheels with a capacity up to 400 L for lifting devices—Dimensions and design
4123.5	Part 5: Performance requirements and test methods
4123.6	Part 6: Health, safety and environment
4123.7	Part 7: Colours, markings and designation requirements

BS EN

1501	Refuse collection vehicles and their associated lifting devices—General requirements and safety requirements
1501-1	Part 1: Rear-end loaded refuse collection vehicle

3 DEFINITIONS

For the purposes of this Standard, the definitions below apply.

NOTE: Terms for components of mobile waste containers and lifting devices, including illustrations are given in Appendix A of AS 4123.1—2008.

3.1 Capacity

The nominal volume of mobile waste containers from 500 L to 1200 L with flat lids as stated in accordance to Table 1.

NOTE: Nominal volume is stated without the tolerances.

3.2 Functional and safety dimensions

Essential dimensions which ensure the functionality and interchangeability of the container with the compatible lifting device and which are necessary for the operator's safety and health.

3.3 Lifting device

A device that picks up locates, aligns, securely locks, tilts, empties waste container into the hopper and returns it back on the ground.

This is a free preview. Purchase the entire publication at the link below:

AS 4123.2 : 2008 : EN : COMBINED PDF

- ⊙ Looking for additional Standards? Visit SAI Global Infostore
- ⊙ Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation

Need to speak with a Customer Service Representative - Contact Us